

PL34 Plinth Standpipe

with 3/4" Brass Bib Tap (Mark III)

Manufactured in high quality stainless steel, the Edwards Plinth models offer the advantage of ground-based installation, while still offering a safe and secure water supply,

The units are manufactured with quality and security in mind, complete with lockable covers to prevent misuse and vandalism. The internal plumbing is insulated to offer protection against climatic change, however during severe cold weather conditions, it is important that the unit should be drained to avoid frost damage.

Also Available with TYPE ESRS Self Regulating Heating Tape (Wattage: 10Watts @ 10DegC ; Voltage: 240V). www.eshltd.com. Please call 01584 861223 or email for further information.

N.B. The water user must decide upon the backflow requirements necessary for each installation.

PL34 Standpipe Specification:

PL34 Shell	
Material	Brushed Stainless Steel (Grade 304 - 1.5mm Thickness)
Unit Length	820mm
Unit Section	106mm x 106mm
Outlet Tap Cover	225mm x 180mm x 120mm
Stop Tap Cover	70mm x 260mm x 110mm
Stabilising Base Plate	255mm x 205mm

PL34 Plumbing	
Double Check Value	22mm DCV (WRAS Approved)
Outlet Tap	3/4" Brass Bib Tap
Stop Tap	22mm Brass Stop Tap
Drain Off Tap	Type A. Brass Drain Valve
Mains Connection	3/4" BSP Brass Female Socket
Internal Rising Main	22mm Polypipe
Insulation	Polyflex expanded foam or equivalent insulator, giving protection down to -5 degrees Celsius

